

Preliminary

HTM-1907R

19 inch Flat-surface HDTV/SDTV Multi-Format Color Monitor



Evolutionary New Features

- A new Flat Surface and High Resolution CRT is employed to achieve superb picture quality.
- Optional New Multi SDI Modules have been developed for the HTM series Multi-Format monitors. These modules accept HD-SDI or SD-SDI by auto detection. Also can be equipped with Embedded Audio Outputs (Analog or AES/EBU) and Audio Level Indicators (4ch or 8ch).

■ Features

- 900 TV Lines and Broadcast Quality.
- 1080i, 720p, 1080/24pSF, NTSC and PAL are available (Including Option)
- HDTV /SDTV analog component input signals are standard.
- Rear access plug-in modules for SDI (multi-format) and NTSC or PAL input signals available as options. Up to four modules can be plugged into the monitor.
- Plug-in module design allows for future system extension and easy maintenance.
- Auto-set up probe can adjust for desired color temperature. (Option)

■ Specifications

General

- Power Requirements : 100V-120VAC +/- 10%
- Power Consumption: 200W
(240W MAX with full options)
- Ambient Temperature:
0-40 degree C (32-104 degree F)
- Humidity:
90% or less relative humidity (No Condensation)
- Dimensions:
450(W) x 399(H) x 515(D) mm, or
17.7(W) x 15.7(H) x 20.3(D) inch
- Weight: approx. 37kgs (81.57lbs)

Rating

- Input Signal
HDTV
RGB/Y,PB,PR signal: BNC 1 input (loop-through)
Acceptable formats:
1080/60i or 59.94i, 1035/60i or 59.94i
720/60p or 59.94p, 1080/24pSF
2nd channel analog component and SDI inputs can be added by installing optional modules

SDTV
RGB(Y,PB,PR signal): BNC 1 input (loop-through)
Acceptable formats : 480i/59.94, 575i/50
Same inputs as HDTV
2nd channel analog component, SDI, and NTSC or PAL encoded inputs can be added by installing optional modules

Performance

- CRT: In-line gun, Dot-shadow mask, high resolution Flat surface CRT
- Dot Trio Pitch: 0.25mm
- Horizontal Resolution (at picture center) :
900 TV lines or more (in HDTV)
- Light Transmission (at center) : 79%

Video Signal System

- Frequency Response: 60Hz -25MHz +1dB/-3dB
- Noise: Coherent Noise: -46dB or more
Hum Noise: -50dB or more
Random Noise: -50dB or more

Deflection/SYNC System

- Scan
HDTV:
Normal scan (16:9) / Under scan (16:9) / HD 4:3 scan
(The expansion of 4: 3 area)
SDTV:
Normal scan (4:3/16:9) / Under scan (4:3/16:9)
- Convergence
Within circle of 90% of picture height:
within 0.3mm
- Within circle of 90% of picture width:
within 0.4mm

Design and specifications are subject to change without notice.

Ikegami Electronics (U.S.A.) Inc

URL: <http://www.ikegami.com>

Headquarters	37 Brook Avenue, Maywood, NJ 07607 Phone: (201)368-9171 Fax: (201)569-1626
Westcoast office	2631 Manhattan Beach Blvd., Redondo Beach, CA 90278 Phone: (310)297-1900 Fax (310)536-9550
Southwest office	526 Bluebird Lane, Red Oak, TX 75154 Phone: (972)869-2363 Fax: (972)556-1057
Midwest office	747 Church Road, Unit C1, Elmhurst, IL 60126 Phone: (630)834-9774 Fax: (630)834-8689
Southeast office	5200 N.W. 33rd Avenue, Suite 111, Ft. Lauderdale, FL 33309 Phone: (954)735-2203 Fax: (954)735-2227