

Ikegami®

7-inch Stand alone Video Monitor **V-R70DP**



The V-R70DP is the successor to the V-R70P. Significant improvements over the previous model include our Completely Digital TFT-MegapixelT high resolution LCD screen with 1.2 million pixels, V-Mount battery adapter, 4 pin XLR power jack, and optical grade polycarbonate screen protection. Analog signals are digitized using an advanced 10 bit process with 4x over sampling and adaptive 5 line comb filter plus exacting color space conversion. Video is scaled to fit on screen in the highest resolution using a state of the art LSI that incorporates 4 x 4 pixel interpolation with precision Gamma correction to produce the best images available.

- Durable metal enclosure
- "V" Mount battery adapter included
- Runs 4 to 6 hours on optional 50WH battery
- High Resolution 7-inch wide screen 800x480 Dots with 1.2 million pixels
- Optical grade polycarbonate screen cover with Antireflective/Antiglare coating
- 100% digital processing
- Analog signals converted to 10 bit digital
- High resolution scaling of all images
- Wide viewing radius - 130° horizontal and 120° vertical provides superior visibility when the viewer is not directly in front of the screen
- 380 candelas per square meter (cd/m²) luminance produces enhanced image quality in varying light and viewing conditions

- 400:1 ratio of contrast between black and white luminance values with response rates less than 30 ms results in excellent quality for moving images
- 4:3 and 16:9 screen aspect ratios
- Automatic NTSC/PAL format detection
- Standard inputs:
 - Composite Video PAL/NTSC with loop output
 - 4 Pin XLR D.C. power jack
- Easy to see three color tally indicators
- Built in Color Bars
- Blue Screen for color adjustment
- Adjustment Settings Memory
- Includes ¼-20 mounting plate that can be attached to any edge of the enclosure (additional mounting plates available)
- Includes universal voltage Class-2 power supply
- Fits into Tektronix® WFM7F05/1700F05 rack adapter
- Optional rack mount kit

■ SPECIFICATIONS:

Viewing Area:	6.14" (H) x 3.27" (V)
Aspect Ratio:	4 : 3
Pixels:	800 (H) x RGB x 480 (V)
Dot Pitch:	0.065mm x 0.175mm
Display:	7" 1.2 Megapixel TFT
Brightness:	380 cd
Power Requirement:	10-17 VDC, 600m Amp.

Video Input:	1 x S-Video 2x Composite
Dimensions:	Width 7.6 Inch Height 5.16 Inch Depth 2.16 Inch Weight 1.8 lbs.

Design and specifications are subject to change without notice.

Ikegami Ikegami Electronics (U. S. A.) Inc.

■ URL <http://www.ikegami.com>

Headquarters	37 Brook Avenue, Maywood, New Jersey 07607 Phone 201-368-9171 Fax 201-569-1626
West Coast Office	2631 Manhattan Beach Blvd., Redondo Beach, CA 90278 Phone 310-297-1900 Fax 310-536-9550
Southwest Office	773 Bearden Waxahachie, TX 75167 Phone 972-869-2363 Fax 972-556-1057
Midwest Office	747 Church Road, Unit C1, Elmhurst, IL 60126 Phone 630-834-9774 Fax 630-834-8689
Southeast Office	5200 N.W. 33rd Ave. Suite 111, Ft. Lauderdale, FL 33309 Phone 954-735-2203 Fax 954-735-2227