



ECO-D12-2812

IR Vandal Resistant
Color Dome Camera

The latest addition to our Eco Series camera line, is the ECO-D12-2812. A high resolution low illumination vandal resistant IR color dome camera defined by broadcast industry specialists to meet the stringent demands of today's CCTV Professional.

ECO-D12-2812 with outstanding high resolution images at 750TVL, True Day/Night, On Screen Display, Smart IR's, 30 Infrared LEDs with 850nm with a range of over 130", DWDR, IP66 Weather resistant, Vandal-proof and extreme operating temperature down to -40 degrees, are some of the best features in this ECO Series line camera.

Features:

- Exceptional resolution of over 750 horizontal TV lines for amazing image quality
- 960H CCD sensor with high IR sensitivity
- True Day/Night zero light operating range of 130 feet or more from 30 IR LEDs (scene reflectivity dependent)
- Smart automatic exposure level adjust to achieve the desired IR brightness in a user defined area
- Simple and easy to use OSD setup menu
 - Digital Wide Dynamic Range for proper contrast in challenging bright or unbalanced scene lighting conditions
 - Anti Color Roll for proper white balance
 - Programmable Back Light Compensation (BLC) and Highlight Compensation (HLC)
 - Adjustable 2D-Noise Reduction to increase low light picture clarity and save DVR HDD disk space
 - Privacy masking for 8 configurable zones
 - Lens shading compensation for even exposure out to the lens periphery
- 2.8~12mm 2 Megapixel Aspheric Varifocal DC iris lens to capture the desired field of view
- Dual voltage (12VDC/24VAC)
- IP66 weather resistant
- -40 degrees Extreme Operating temperature
- Service Video output for convenient installation, and ease of service
- 3-Axis gimbal for convenient wall or ceiling mounting
- Flush or Surface mountable (surface mounting/splice box fits standard 3/4" conduit and electrical boxes)
- Optional wall mount bracket with 3/4" conduit fitting.

300 E Route 17S, Mahwah, NJ 07430
(201)-368-9171 , cctv@ikegami.com



ECO-D12-2812

IR Vandal Resistant Color Dome Camera

Specifications:

Imaging Device	1/3" 960H High Sensitivity CCD
Video Format	NTSC
Picture Elements	NTSC: 1020(H)x508(V)
Effective Picture Elements	NTSC: 976(H) x 494(V)
Horizontal Resolution	More than 750 TVL
Sensitivity	0 lux IR on; .01 lux native from sensor
IR LED	30 LEDs, 850nm
IR Range*	131' (* As with all IR cameras, IR range will vary based on scene IR reflectivity and illumination)
Smart IR Exposure Adjust	Off/On; adjustable for gain, size and location of sensing area
S/N Ratio	Over 50dB (AGC off)
Video Output	BNC 1.0V p-p 75Ω; video test point inside dome, cable supplied
Gamma Correction	0.45
Lens Type	2 Megapixel Aspheric Varifocal DC Iris 2.8~12mm F=1.6
Lens Positioning	3-axis flexible positioning for wall or ceiling mounting
Back Light Compensation	OFF/BLC/HLC Selectable
Auto Gain Control	Off/Low/Middle/High
Electronic Shutter	Auto; or 1/60, FLK, 1/250, 1/500, 1/1000, 1/2000, 1/4000, 1/5000, 1/10000, 1/100000
White Balance	ATW/AWB/AWC->SET/Anti-Color Roll/Manual
Sync. Mode	Internal (plus Anti-Color Roll White Balance option above)
Day & Night	Auto True D/N with motorized ICR; controlled by photo sensor. Choose Auto, color or B/W
OSD Menu	Multiple functions using 3-axis joystick
OSD Languages	English, Spanish, Portuguese, German, Russian, Japanese, Chinese, French
2D-DNR	On/Off (Level Adjustable)
Digital Wide Dynamic Range	On/Off (Level Adjustable)
Mirror	Off/On
Motion Detection	Off/On for 4 selectable zones (On screen indication)
Privacy Mask	Off/On for 8 selectable zones
Lens Shading Correction	Off/On with adjustable level and center
Other OSD Functions	Camera Title with position, Font Color, Image Contrast/Sharpness, CRT/LCD display optimization, Negative Image, DPC (Dead Pixel Compensation)
Power Source	12VDC/24VAC
Power Consumption	12VDC:420mA max. / 24VAC:4.8W max.
Operating Temperature	-40°F~140°F ; -40°C~60°C
Environmental	IP66 weather resistant
Mechanical	Vandal proof dome; back box accepts 3/4" conduit fittings and hole pattern matches various standard electrical boxes; remove back box for flush mounting
Dimensions	Surface: 6.14"/156mm dia. x 5.1"/129.5mm high Flush: 5.63"/143mm dia. X 3.11"/79mm visible & .98"/25mm behind surface
Weight	1.2 pounds flush mounted
Certifications	CE , FCC, RoHS
Environmental	IP66 weather resistant

Design subject to change without notice.

300 E Route 17S, Mahwah, NJ 07430
(201)-368-9171 , cctv@ikegami.com