



ECO SERIES

EE-IPB10MZ

3MP IP HD Color
Bullet Camera

Our IP High Definition Outdoor Color Bullet Camera with IR's, was defined by industry specialists to meet the stringent demands of today's CCTV Professional.

The latest addition to our quality line of cameras, is the **EE-IPB10MZ** which comes with an impressive 3MP of amazing image quality, ONVIF Compliance, useful D-WDR, motorized zoom lens, plus the added benefit of Day/Night ICR auto switch for best low illumination performance capacity, resulting in higher sensitivity at lower light levels.

Features:

- 1/3" 3MP HD CMOS Sensor
- Effective Pixels: 2048(H) × 1536(V)
- 30fps @ 3MP
- View IP Video in Real Time over the Internet
- 2.8 ~ 12mm Motorized Lens
- Zooming Control via Internet
- 48 IR with 0 Lux
- ICR auto switches between Day & Night Time
- 3D DNR
- Digital-WDR
- BNC Output
- Two way Audio
- Smart In & Out Alarm
- Motion Detection
- IP66 Weatherproof
- 12V DC/PoE

Suggested Use:

- Outdoor
- Financial
- Retail
- Government
- Education
- Retail
- Parking Garage

Specifications	
Image Sensor	1/3" 3MP HD CMOS Sensor
Effective Pixels	2048 x 1536
Electronic Shutter	1/60-1/100,000Sec (NTSC)
Mini. Illumination	0 Lux (IR ON)
Video Output	BNC ×1
IR LEDs	48 IR
IR LEDs Distance	98 ~ 164ft (30-50 m)
Day / Night	ICR
Noise Reduction	3D Noise Reduction
WDR	Digital-WDR
Focal Lens	2.8 ~ 12mm Motorized Lens / Mount type Φ14
ROI	Yes
Audio In	MIC IN × 1
Audio Out	MIC OUT ×1
Recording Resolution	3MP(2048×1536) / 1080 P(1920×1080) / 720P (1280×720) / D1 / CIF / 480×240
Record Rate	3MP (1~30fps) / 1920×1080 (1~30fps) / 1280×720 (1~10fps) / D1 (1~30fps) / CIF (1~30fps) / CIF (1~30fps) / 480×240 (1~30fps)
Bit Rate	64Kbps ~ 8Mbps
Backup Mode	microSD, up to 64GB
Alarm In	IN x 1CH
Alarm Out	OUT x 1CH
Ethernet	RJ45
Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP ; ONVIF
Max User Access	Supports simultaneous monitoring for up to 10 users; Support multi-stream real time transmission
Smart Phone	Phone, Android, Windows phone
Compatibility	ONVIF
RS485	Support RS485
Alarm	Motion / Sensor Alarm
Power Supply	DC 12V / PoE
Power Consumption	< 3.5W (ICR OFF) / < 8W (ICR ON)
Working Environment	-40°F ~ 122°F (-40°C ~ 50°C), 10% ~90% Humidity
Protection	IP66
Dimensions	4.3" x 11.2" (Φ109mm × 284mm)
Weight	2.4lbs (1107g)

Design and specifications are subject to Change without notice.

37 Brook Avenue, Maywood, NJ 07607
Phone (201)368-9171 Fax (201)569-1626
email: cctv@ikegami.com