



# ECO SERIES

## EE-IPB10 3MP IP HD Color Bullet Camera

Our IP High Definition Outdoor Color Bullet Camera with IR's, was defined by industry specialists to meet the stringent demands of today's CCTV Professional.

The latest addition to our quality line of cameras, is the EE-IPB10 which comes with an impressive 3MP of amazing image quality, ONVIF Compliance, useful D-WDR, plus the added benefit of Day/Night ICR auto switch for best low illumination performance capacity, resulting in higher sensitivity at lower light levels.

### Features:

- 1/3" 3Mp HD CMOS Sensor
- Effective Pixels: 2048(H) × 1536(V)
- 30fps @ 3Mp
- 2.8 ~ 12mm Varifocal Lens
- 48 IR with 0 Lux
- 3D DNR
- Digital-WDR
- BNC Output
- Audio In
- Smart In & Out Alarm
- Motion Detection
- MicroSD Storage
- IP66 Weatherproof
- 12V DC/PoE

### Suggested Use:

- Outdoor
- Financial
- Retail
- Government
- Education
- Retail
- Parking Garage

Specifications	
Image Sensor	1/3" 3Mp HD CMOS Sensor
Effective Pixels	2048 x 1536
Electronic Shutter	1/25s ~ 1/100,000s
Mini. Illumination	0 Lux (IR ON)
Video Output	BNC x1
IR LEDs	48 IR
IR LEDs Distance	98 ~ 164ft (30-50 m)
Day / Night	ICR
Noise Reduction	3D Noise Reduction
WDR	Digital-WDR
Focal Lens	2.8 ~ 12mm Vari-Focal Lens; Fixed Iris
ROI	Yes
Audio In	MIC IN x 1
Audio Out	MIC OUT x1
Recording Resolution	3MP(2048 x1536) / 1080 P(1920 x 1080) / 720P (1280 x 720) / D1 / CIF / 480 x240
Record Rate	3MP (1~30fps) / 1920 x1080 (1~30fps) / 1280 x720 (1~10fps) / D1 (1~30fps) / CIF (1~30fps) / CIF (1~30fps) / 480 x240 (1~30fps)
Bit Rate	64Kbps ~ 8Mbps
Backup Mode	microSD, up to 64GB
Alarm In	IN x 1CH
Alarm Out	OUT x 1CH
Ethernet	RJ45
Protocol	TCP/IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP ; ONVIF
Max User Access	Supports simultaneous monitoring for up to 10 users; Support multi-stream real time transmission
Smart Phone	Phone, Android, Windows phone
Compatibility	ONVIF
RS485	Support RS485
Alarm	Motion / Sensor Alarm
Power Supply	DC 12V / PoE
Power Consumption	< 3.5W (ICR OFF) / < 8W (ICR ON)
Working Environment	-40°F ~ 122°F (-40°C ~ 50°C), 10% ~90% Humidity
Protection	IP66
Dimensions	4.3" x 11.2" (Φ109mm x 284mm)
Weight	2.4lbs (1107g)

Design and specifications are subject to Change without notice.

37 Brook Avenue, Maywood, NJ 07607  
 Phone (201)368-9171 Fax (201)569-1626  
 email: cctv@ikegami.com