



ECO SERIES

EE-IPHD3MPD

3MP HD VR IR Motorized
Lens Color Dome Camera

Our IP High Definition Vandal Resistant Color Dome Camera with IR's, was defined by industry specialists to meet the stringent demands of today's CCTV Professional.

The latest addition to our quality line of cameras, is the EE-IPHD3MPD which comes with an impressive 3MP of amazing image quality, ONVIF Compliance, useful D-WDR, plus the added benefit of Day/Night ICR auto switch for best low illumination performance capacity, resulting in higher sensitivity at lower light levels.

Features:

- 1/3" 3MP HD CMOS Sensor
- Effective Pixels: 2048(H) × 1536(V)
- 30fps @ 3MP
- 2.8 ~ 12mm Motorized Lens
- 30 IR with 0 Lux
- 2D / 3D DNR
- Digital-WDR
- BNC Output
- 2-way Audio
- Smart In & Out Alarm
- MicroSD Storage
- IP66 & IK10 Protection
- 12V DC/PoE

Suggested Use:

- Outdoor
- Financial
- Retail
- Government
- Education
- Retail
- Parking Garage

Specifications	
Image Sensor	1/3" 3MP CMOS Sensor
Effective Pixels	2048 × 1536
Electronic Shutter	1/25s~1/100000s
Mini. Illumination	0 Lux (IR On)
IR LEDs	30 IR
IR LEDs Distance	66 ~ 98ft (20~30m)
Day / Night	ICR Auto Switch
Noise Reduction	3D Noise Reduction
WDR	Digital WDR
Lens	
Focal Lens	2.8 ~ 12 mm Motorized Lens
ROI	Yes
Image Settings	Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR., etc. (Adjustable through Client Software / Web Browser)
Audio In	MIC IN x 1CH
Audio Out	MIC OUT x 1CH
Recording Resolution	3MP [2048 × 1536] / 1080P [1920 × 1080] / 720P [1280 × 720] / D1 / CIF / 480 × 240
Record Rate	3MP [1~30fps] / 1920 × 1080 [1~30fps] 1280 × 720 [1~10fps] / D1 [1~30fps] / CIF [1~30fps] / CIF [1~30fps] / 480 × 240 [1~30fps]
Bit Rate	64Kbps ~ 8Mbps
Backup Mode	MicroSD up to 64GB
Alarm In	IN x 1CH
Alarm Out	OUT x 1CH
Ethernet	RJ45
Remote Connections	IE Browser, CMS Remote Control
Protocol	TCP/IP, DHCP, PPPoE, DDNS, SMTP, UPnP, RTSP, NTP
Max User Access	Supported simultaneous monitoring for up to 10 users; multi-stream real time transmission
Smart Phone	iPhone, Android, Windows phone
Compatibility	ONVIF, GB-T/28181-2011
RS485	Yes
Alarm	Motion / Sensor Alarm
Power Supply	DC 12V / PoE
Power Consumption	< 3W (ICR OFF) / < 5.5W (ICR ON)
Working Environment	-40°F ~ 122°F (-40°C~50°C), 10% ~ 90% Humidity
Protection	IP66 & IK10
Dimensions	5.9" x 4.5" (Φ150mm × 114mm)
Weight	2.2lbs (990g)

Design and specifications are subject to Change without notice.

37 Brook Avenue, Maywood, NJ 07607
Phone (201)368-9171 Fax (201)569-1626
email: cctv@ikegami.com