

Ikegami's high performing, industrial grade LCD monitor is feature rich that includes wide screen size, 1080p resolution, 1400:1 contrast, PIP/PBP, 16.7 million colors, robust all metal cabinet, dual analog input/outputs, dual HDMI inputs and superb noise reduction.

The LCM-420A monitor provides flexibility and configuration selections essential in supporting your security surveillance applications




High Performance, Industrial Grade, Large Screen 42 inch CCTV LCD Monitor

FEATURES

- Large Screen Size for the multi-purpose applications.
- 1980 x 1080 @60Hz resolution.
- High Brightness and Contrast Ratio.
- Built-in 3D Comb Filter and Deinterlace.
- Various Video Interface built-in for CCTV applications.
- Built-in Speakers for the alarm.
- Desktop Stand as standard.
- Optional VESA wall mounts and ceiling mounts are available

Dimensions



Optional Mounts Available



LCM-420A 42-inch High Performance LCD Monitor

Specifications:

Display	Screen Size	LCM-420A
	Max. Resolution	1920 x 1080 @60Hz
	Pixel Pitch	0.483 x 0.483 mm
	Brightness	350cd/m ²
	Contrast Ratio	1400: 1
	Aspect Ratio	16 : 9
	Viewing Angle(H/V)	178°/178°
	Display Color	16.7 Million
	Response Time	< 8ms(Gray to Gray)
	Video System	NTSC / PAL
	Frequency(H)	30 - 80 KHz(H)
	Frequency(V)	56 - 75 KHz(V)
Interface	Video In/ Out(BNC Type)	2 / 2
	S-Video In/ Out	1 / 1
	VGA In(15Pin D-Sub)	1
	Component	1
	DVI-D In/ HDMI In	1 / 2
	Audio In /Out(RCA type)	2 / 1
	PC Stereo In	1 / 1
Audio	Built in Speakers	7.5W x 2
Transmitter	Remote Control	Yes
Special Features	Multi Display Function	PIP / PBP
	Filter Type	3D Comb filter / Deinterlace
	LCD Protection Glass	No
	Rack Mountable Kit	Optional Wall mount
	Multilingual Language	English, Spanish, French, German, Italian
Dimension	Outline Dimension (with stance)	37.95" x 24.41" x 9.45"
	Net Weight	72.1 lbs
Cabinet	Finish / Tilt Stand	Black (Metal) / Yes
	MTBF(Approx.)	50,000 Hours
Regulations		CB, FCC(A), CE-Emc(LVD)
Power	Consumption : < On	<150W
	Electrical Ratings	AC100 - 240V(50/60Hz)
Circumstance	Operating Temperature	10 - 40°C / 50 - 104°F
Mounts	VESA Mounts Size	400 X 300 mm

Design and specifications are subject to Change without notice.

IKEGAMI ELECTRONICS, (U.S.A.) INC.

URL: <http://www.ikegami.com> email: cctv@ikegami.com

Headquarters	37 Brook Avenue, Maywood, NJ 07607 Phone (201)368-9171 Fax (201)569-1626
West Coast	Redondo Beach, CA 90278 Ph (310)297-1900 Fax (310)536-9550
South West	Waxahachie, TX 75167 Ph (972)869-2363 Fax (972)556-1057
South East	Deerfield Beach, FL 33441 Ph (954)571-7177 Fax (954)571-7760
Midwest	Bloomington, IL 60108 Ph (603)-372-8777 Fax (603)-372-8777